

# ENERGY STAR® Power and Performance Data Sheet

Model Name: MAGNIA R3320b



## System Characteristics

Form Factor	2 socket rack server
Available Processor Sockets	2
Available DIMM Slots / Max Memory Capacity	12slots / 384GB max.
ECC and/or Fully Buffered DIMMs	DDR3-1600 ECC DIMMs
Available Expansion Slots	6
Minimum and Maximum # of Hard Drives	Min.: 1unit ; Max: 26units
Redundant Power Supply Capable?	Yes
Power Supply Make and Model	Delta Electronics DPS-800QB A
Power Supply Output Rating* (watts)	800W
Minimum and Maximum # of Power Supplies	1 to 2
Input Power Range (AC or DC)	115Vac and 230Vac
Power Supply Efficiency at Specified Loadings*	87.40@10%, 91.67@20%, 94.09@50%, 91.95@100%
Power Supply Power Factor at Specified Loadings*	0.89@10%,0.96 @20%, 0.99@50%, 0.99@100%
Operating Systems Supported	Microsoft Windows Server 2008 R2 Standard Microsoft Windows Server 2008 R2 Enterprise etc.
Installed Operating System for Testing	Microsoft Windows Server 2008 R2 Standard

\* Note: Power supply information is for a single power supply only

## System Configurations

	Minimum	Typical	Maximum
Configuration ID	SYU4610C	SYU4610C	SYU4611B
Processor Information	Intel Xeon E5-2420 1.90GHz x2	Intel Xeon E5-2420 1.90GHz x2	Intel Xeon E5-2430 2.20GHz x2
Memory Information	DDR3-1600 2GB x2	DDR3-1600 32GB x6	DDR3-1600 32GB x12
Internal Storage	SATA 6Gbps 7200rpm 250GB x1	SAS 6Gbps 10000rpm 900GB x3	SAS 6Gbps 10000rpm 900GB x26
I/O Devices	None	SAS Raid Card x1	SAS Raid Card x2 Ethernet card x4
Power Supply Number and Redundancy Configuration	Delta DPS-800QA 800W x1	Delta DPS-800QA 800W x2	Delta DPS-800QA 800W x2
Management Controller or Service Processor Installed?	Yes	Yes	Yes
Other Hardware Features / Accessories			

## Power Data

	Minimum	Typical	Maximum
Idle Category (1S and 2S only)	Category D: Managed Dual Installed Processor (2P) Servers		
ENERGY STAR Idle Power Allowance (1S and 2S only)	150W	594W	1224W
Measured Idle Power (watts)	77.3	128.2	354.5
Power at Full Load* (watts)	137.6	189.5	444.1
Benchmark / Method Used for Full Load Test	Use SiSoftware Sandra Engineer (.NET Multi-Media)		
Test Voltage and Frequency for Idle and Full Load Test	230V / 60Hz		
Range of Total Estimated Energy Usage ** (kWh/year)	1,354 to 2,411	2,246 to 3,320	6,211 to 7,781
Link to Detailed Power Calculator (if available)			

\* Note: Full load power represents the sustained, average power at 100% load of the given workload, and does not necessarily represent the absolute peak power or the highest average, sustained power possible for other workloads.

\*\* Note: Estimated kWh/year gives the absolute range of energy use a user could expect from continuous operation (24x7x365) and ranges from 100% Idle usage to 100% full load operation. The calculation also includes typical data center overhead at a ratio of 1 watt of overhead to every 1 watt of IT load (corresponding to a PUE of 2.0). Closer approximations may be found by using established power calculators and specific information about the intended operating environment (e.g., average time at Idle, data center PUE, etc.).

## Power and Performance for Benchmark #1

	Minimum	Typical	Maximum
Benchmark Used and Type of Workload	SiSoftware Sandra Engineer (.NET Multi-Media)		
Avg. Power Measured During Benchmark Run	137.6W	189.5W	444.1W
Benchmark Performance Score	50.81Mpixel/s	50.85Mpixel/s	57.52Mpixel/s
Power Performance Ratio (perf score/avg. power)	0.37	0.27	0.13
Link to Full Benchmark Report (Where Available)	N/A	N/A	N/A

## Power and Performance for Benchmark #2 (optional)

	Minimum	Typical	Maximum
Benchmark Used and Type of Workload			
Avg. Power Measured During Benchmark Run			
Benchmark Performance Score			
Power Performance Ratio (perf score/avg. power)			
Link to Full Benchmark Report (Where Available)			

# ENERGY STAR Power and Performance Data Sheet

Model Name: MAGNIA R3320b



<b>Power Saving Features</b>	<b>Enabled on Shipment</b>	<b>End-User Enabling Required</b>
Processor Dynamic Voltage and Frequency Scaling	<b>Yes</b>	<b>No</b>
Processor or Core Reduced Power States	<b>Yes</b>	<b>No</b>
Power Capping	<b>No</b>	<b>Yes</b>
Variable Speed Fan Control Based on Power or Thermal Readings	<b>Yes</b>	<b>No</b>
Low Power Memory States	<b>No</b>	<b>No</b>
Low Power I/O States	<b>No</b>	<b>No</b>
Liquid Cooling Capability	<b>No</b>	<b>No</b>
Other1:		
Other2:		
Other3:		
Other4:		

### Power and Temperature Measurement and Reporting

Input Power Available & Accuracy?	Yes, +/- 5% for 80W-800W, +/-10W for ~100W
Input Air Temp Available & Accuracy?	Yes, +/- 2(c)
Processor Utilization Available?	Yes
Other Data Measurements Available & Accuracy?	
Compatible Protocols for Data Collection	IPMI
Averaging method and time period	Non Averaging, 1 sec. interval sampling.

### Thermal Information \*

	<b>Minimum</b>	<b>Typical</b>	<b>Maximum</b>
Total Power Dissipation (watts)	137.6W	189.5W	444.1W
Delta Temperature at Exhaust at Peak Temp. (°C)	2.7	3.8	8.1
Airflow at Maximum Fan Speed (CFM) at Peak Temp.	96.3	198.2	110.6
Airflow at Nominal Fan Speed (CFM) at Nominal Temp.	62.8	60.2	52.6

\* References: ASHRAE Extended Environmental Envelope Final August 1, 2008  
 Thermal Guidelines for Data Processing Environments, ASHRAE, 2004, ISBN 1-931862-43-5  
 Peak temperature is defined as 35 °C, Nominal Temperature is defined as 18 - 27 °C

### Notes

1. SPECpower\_ssj2008 is a registered trademark of the Standard Performance Evaluation Corporation (SPEC). Benchmark results stated above reflect results published on XX/XX/XX. For the latest SPECpower\_ssj2008 benchmark results, visit [http://www.spec.org/power\\_ssj2008](http://www.spec.org/power_ssj2008).

### ENERGY STAR Qualified Configurations

**Include specific information on ENERGY STAR Qualified SKUs or configurations**

Qualified Configuration ID: SYU4610C, SYU4611B, SYU4610D, SYU4612B

## **ENERGY STAR Power and Performance Data Sheet**

Model Name: MAGNIA R3320b

Page 3 of 3



### **ENERGY STAR Qualified Configurations (Continued)**

**Include specific information on ENERGY STAR Qualified SKUs or configurations**

--